

### Interactive PDF

PAGE NAVIGATION

INTERNET LINK



VIDEO/ANIMATION



Version 1.0



# Experience creates trust. Today as in the past.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

#### Introduction

- Applications
- > Benefits
- Technology
- Software
- Tutorials
- Technical Specifications



Successful agriculture production has always been a question of experience and commitment. Wrong decisions can have serious consequences. In today's ever changing environment, nature cannot be fully planned and accurate results cannot always be determined. However, through targeted examination of the process, it can be analyzed better.

With over twenty years of experience in process technology, Carl Zeiss is one of the world leader in the measurement and analysis of continous process applications.

Through continuous collaboration with our customers, we have developed solutions which meet the highest performance demands, for which our customers can depend on in any process oriented situ-

ation. With acknowledged Carl Zeiss competence in hardware, software and engineering, we are able to produce complete systems which can withstand extreme conditions with results that superior to lab measurements

Extremely resilient, extremely precise and extremely reliable – the new Corona extreme.



# High time for a solution. The new Corona extreme.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

#### Introduction

- Applications
- > Benefits
- Technology
- Software
- Tutorials
- Technical Specifications

The quality of natural products is subject to natural fluctuations. Despite the inconsistency in the construction of the sample, consistent quality must be maintained in the final product. In addition, industry standard requirements for processing the materials and related documentation must be maintained. For this to be achieved accurate process control is essential. Process time and raw materials cost can be optimized so that production control can be maximized and waste can be minimized.





Continuously monitoring of samples can delivers much more information about the process. When the measurements are carried out in real-time with the precision of lab results, the process can be precisely optimized to maximize output. The seamless intergration of data into the information streams (traceability) also increases product safety.

With the introduction of the Corona extreme, we are offering our customers a complete solution comprising a spectrometer sensor and intuitive software – which can be tailored to each customers' specific needs.

Applications specific calibration and calibration support can be provided upon request.

# **Customers applications to date. Corona extreme.**

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- > Introduction
- Applications
- Benefits
- Technology
- > Software
- Tutorials
- Technical Specifications

### Field testing/ seed cultivation

	_
Application	analysis on plot harvester
Products	full maize plants, grass, unripe rye
	and wheat, grains such as wheat, rye,
	rapeseed, grain corn
Parameters	determination of dry matter content
	and protein
Result	determination of quality, yield mea-
	surement, evaluation of cultivation
	success during field harvests, cultiva-
	tion of new varieties

#### **Cereals trade**

Application	inspection at transshipment points
Products	grains such as wheat
Parameters	measurement of moisture, protein,
	gluten, hardness, determination of
	quality
Result	sorting, drying and storage, sale in
	accordance with specification

### **Grain processing**

Application	measurement on delivery
Products	grains such as wheat
Parameters	measurement of moisture, protein,
	gluten, hardness
Application	measurement during processing
Parameters	measurement of moisture, protein
	content, ash content and starch for
	process control
Result	guarantee of quality







### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

>	Introd	uction

# Applications

- Benefits
- Technology
- Software
- Tutorials
- Technical Specifications

# Bioenergy

5,	
Application	measurement on delivery
Products	maize silage, grass silage, whole plant
	silage (renewable resources), liquid
	manure, residual materials
Parameters	evaluation based on potential gas
	input – gas generation potential
Application	measurement during process
Parameters	stability of fermentation based on
	individual acids
Result	process control and optimization
	(room load, retention period)

# Feeding stuff / animal feed

	Application	measurement on delivery
	Products	feeding stuff / animal feed
Parameters measurement of energy co		measurement of energy content
		(proteins, fiber fractions such as ADF,
		NDF, lignin, cellulose, hemicellulose)
	Result	process control and optimization
		(mixing processes) for the production
		of concentrated feed

### Fertilization

Application	measurement during or before spreading
Products	farmyard manure
Parameters	measurement of nitrogen, ammoniacal
	nitrogen, phosphorous, potassium
Result	process optimization, compliance with
	legal stipulations, process optimization,
	saving the cost of chemical fertilizers
	and targeted spreading in order to
	influence the quality of the harvest







# Precision decides. Every day, in real-time.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- Introduction
- Application
- **Benefits**
- Technology
- Software
- Tutorials
- **Technical Specifications**

















Start Animation

Few other spectrometer system from Carl Zeiss incorporates as much application-related experience as the new Corona extreme.

This compact system is easy to install and may be used immediately after a short warm-up period.

The Corona extreme system can be operated independently using the embedded controller which enables a direct evaluation and output of the predicted data.

The spectrometer features fiber free, high energy illumination with outstanding optical properties and internal referencing.

Thus, reliable measurement results are provided for each sample. Within the Corona product family, the instrument calibration may be transferred from one measurement system to another. The instrument data communication are designed for a customer or user specific interface: ISO Bus, Ethernet, Digital IO.

# Reliability creates safety. Today, tomorrow and in the future.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- Introduction
- Applications
- > Benefits
- > Technology
- Software
- > Tutorials
- Technical Specifications

The idea for creating the Corona extreme was for the measuring sensor to become a core component of the process.

In order to accomplish this the extreme conditions under which processes run a were regarded as a the normal environment for the spectrometer system in practice – and not just for short term use, but for the entire product life cycle. For the Corona extreme, this concept was so successful that it gave the system its name.

The integrated measuring head and the compact design incorporating a sapphire flange guarantees protection of the sensor at the interface with the material flow. The Corona extreme is designed to withstand shock values which exceed governmental standards. With 50 g shock resistance, it exceeds all other systems by far and is ideally suited for daily use in the field.

The layout of the other environmental parameters has also been designed in accordance with the possible applications.

This means that Corona extreme can precisely produce measurement data in temperatures ranging from –15 to +50°C in both moist and dusty conditions.

The spectrometer system is protected from supply voltage fluctuations and may be easily connected to a vehicle's on-board power supply. Due to its excellent optical design, the Corona extreme can also be used in labs.















# **Corona extreme**

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- > Introduction
- Applications
- Benefits
- Technology
- Software
- > Tutorials
- Technical Specifications





### 1 Spectrometer

- plane grating spectrometer (PGS)
- internal b/w referencing
- two versions (with and without embedded PC)

### 2 Housing

■ IP 66 housing

### 3 Interfaces

- innovative plug design
- Ethernet interface, optional ISO BUS (CAN BUS)

# 4 Measuring head

- low voltage halogen lamps, longer service life 20.000 hours
- robust sapphire flange for connection to harvesting machinery and closed systems

# User-friendly and powerful. InProcess.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- > Introduction
- Applications
- Benefits
- Technology
- > Software
- > Tutorials
- Technical Specifications



# The InProcess software was developed specially for Corona extreme.

This software enables the user to control several spectrometers at the same time. In addition to performance, ease of use is the primary purpose of the software strategy. Thanks to its clear organization, it is intuitive to use for all levels of operators.

The graphic user interface is comprised of icon menus giving it a familiar feel of operation at first sight. In addition, users may configure sequences, calculations and display formats based on their individual requirements.

# Simple, intuitive, efficient.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- > Introduction
- Applications
- Benefits
- Technology
- Software
- > Tutorials
- Technical Specifications

#### Measurement menu

- access to "defined products"
- immediate start of measurement
- display of measurement as value, graph or spectrum
- display of limit values

#### Product set-up menu

- creation of "defined products"
- creation of measurement sequence
- calculation, evaluation and integration into higher-ranking process environment
- adjustment of views
- support of calibrations (chemometric models)
  which are produced using standard chemometric
  software e.g. by GRAMS, UNSCRAMBLER, UCAL
- control of events via Digital I/O

#### User management

 setup of various user groups with different access levels


### Measurement history

- access to previous (completed) measurement runs
- file export

#### **Event history**







# Take the time. Allow us to present the Corona extreme.

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

- > Introduction
- Applications
- > Benefits
- Technology
- Software
- > Tutorials
- Technical Specifications

In terms of their functioning, the Corona extreme system's components have to meet very demanding requirements. The compact spectrometer system is extremely low maintenance and easy to service. The system's functionality is described in detail below.

### First steps

- installation of the system
- measurement with an available product

# Watch it at youtube.com



# Manufacturing a product

- creation of a measurement sequence
- calculation (import calibration)
- display of the results
- display of limit values

# Watch it at youtube.com



# **Technical Specifications**

### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

>	Introduction
>	Applications
>	Benefits
>	Technology
>	Software
>	Tutorials
<b>)</b>	Technical Specifications

	Corona extreme
Spectrometer	diode array spectrometer
Polychromator	PGS
Measurement range	950 – 1650 nm
Mean spectral pixel pitch	3 nm
Spectral resolution (half width at 1/10 max)	≤ 10 nm
Wavelength accuracy	≤ 1 nm
Wavelength reproducibility	≤ 0.1 nm
Light source	halogen
Protection standard	IP 66
Dimensions W x H x D in mm	256 x 190.5 x 253
Weight	10 kg
Range of operating temperatures	−15 °C to +50 °C
Power supply voltage	9–36 V SELV

#### Corona extreme

The new spectrometer system for agribusiness from Carl Zeiss

\	ntron	luctior
,	1111100	luctioi

- Applications
- Benefits
- Technology
- Software
- > Tutorials
- Technical Specifications



# Carl Zeiss Microscopy GmbH

07745 Jena, Germany Optical Sensor Systems

Phone: + 49 (0) 3641 64 2838 Fax: + 49 (0) 3641 64 2485

E-Mail: info.spektralsensorik@zeiss.de

www.zeiss.com/corona-extreme

